

Datum: 01.05.2025

Davčna št.: SI 56119488  
Telefon: 01 500 14 42  
E-mail: [info@podjetje-trg.si](mailto:info@podjetje-trg.si)  
WWW: [www.karcher-trg.si](http://www.karcher-trg.si)

(slika je simbolična)

## Hitre spojke I.D. 7.2, Nerjavno jeklo 1.4305, Fi cevi I.D. 13

Kategorija: [Quick disconnect coupling DN 7.2, with hose stem](#)  
Šifra: **107344RIE**

### Kratek opis

Quick-connect coupling I.D. 7.2, Stainless steel 1.4305, Sleeve I.D. 13, Operating pressure max. 35 bar, Temp. -25 °C to 200 °C

Classic standard coupling type, one side sealing, made of stainless steel.

The closed sleeve protects the coupling from dirt.

We recommend the use of stainless steel plugs and stems!

To prevent injuries or a "whiplash" effect, we recommend that the plug-in nipple is held with one hand during uncoupling.

These quick disconnect couplings are not suitable for direct attachment to pulsating tools.

We recommend using our vibration dampers, according to ISO 6150 § 7.1.

Areas of application: Pneumatic system, machine and plant engineering, measurement, monitoring and control systems, manufacturing industry, chemical / pharmaceutical industry, workshops, automotive, offshore.

### Tehnične Specifikacije

|                              |                                   |
|------------------------------|-----------------------------------|
| Min. sobna temperatura [°C]  | -25                               |
| Min. temperatura medija [°C] | -25                               |
| Merjenje pretoka             | at 6 bar and $\Delta p = 0.5$ bar |
| Ohišje                       | Stainless steel 1.4305            |
| Povezava                     | I.D. 13                           |
| Pritrdilni obroč             | Stainless steel 1.4310            |
| Rokav                        | Stainless steel 1.4305            |
| Telo ventila                 | Stainless steel 1.4305            |
| Tesnilo                      | FKM                               |
| Vzmet                        | Stainless steel 1.4310            |
| Zaporni zatič                | Stainless steel 1.4401            |
| DN                           | 7.2                               |
| a/f [mm]                     | 22                                |
| Max. obratovalni tlak [bar]  | 35                                |
| Dolžina [mm]                 | 59.0                              |
| Max. sobna temperatura [°C]  | 200                               |
| Max. temperatura medija [°C] | 200                               |
| Pretok                       | 1000 l/min (air)                  |