

Hitre spojke I.D. 7.2, ponikljana medenina, cev 10x8

Kategorija: [Quick disconnect coupling DN 7.2, hose connector](#)
Šifra: **107293RIE**

(slika je simbolična)

Kratek opis

Quick-connect coupling I.D. 7.2, nickel-plated brass, Hose connection 10x8, Operating pressure 0 - 35 bar, Temp. -20 °C to 100 °C

Universal, one-hand quick disconnect couplings, one side sealing, suitable for a wide range of tasks and applications! The closed sleeve protects the coupling from dirt.

To prevent injuries or a "whiplash" effect, we recommend that the plug-in nipple is held with one hand during uncoupling.

These quick disconnect couplings are not suitable for direct attachment to pulsating tools.

We recommend using our vibration dampers, according to ISO 6150 § 7.1.

Areas of application: Pneumatic system, machine and plant engineering, measurement, monitoring and control systems, manufacturing industry, medical technology, chemical / pharmaceutical industry, workshops, automotive.

Tehnične Specifikacije

| | |
|------------------------------|--|
| Min. sobna temperatura [°C] | -20 |
| Min. temperatura medija [°C] | -20 |
| Delovni tlak | 0 to 35 bar, maximum static working pressure (non-pulsating) |
| Merjenje pretoka | at 6 bar and $\Delta p = 0.5$ bar |
| Ohišje | Nickel-plated brass |
| Povezava | Hose connection 10x8 |
| Pritrdilni obroč | Stainless steel 1.4310 |
| Rokav | Nickel-plated brass |
| Telo ventila | Brass with a bare metal surface |
| Tesnilo | NBR |
| Vzmet | Stainless steel 1.4310 |
| Zaporni zatič | Stainless steel 1.4034 |
| DN | 7.2 |
| a/f [mm] | 22 |
| Dolžina [mm] | 48.0 |
| Max. sobna temperatura [°C] | 100 |
| Max. temperatura medija [°C] | 100 |
| Pretok | 1000 l/min (air) |