

Datum: 01.06.2026



(slika je simbolična)

## Hitre spojke I.D. 7.2, zunanji navoj medenina, vrteče, 8x6

Kategorija: [Quick disconnect coupling DN 7.2, hose connector](#)  
Šifra: **107226RIE**

### Kratek opis

Quick-connect coupling I.D. 7.2, bright brass, rotating, Connection 8x6, Operating pressure 0 - 35 bar, Temp. -20 °C to 100 °C

"

Universal, one-hand quick disconnect couplings, one side sealing, suitable for a wide range of tasks and applications! The closed sleeve protects the coupling from dirt.

To prevent injuries or a "whiplash" effect, we recommend that the plug-in nipple is held with one hand during uncoupling.

These quick disconnect couplings are not suitable for direct attachment to pulsating tools.

We recommend using our vibration dampers, according to ISO 6150 § 7.1.

Areas of application: Pneumatic system, machine and plant engineering, measurement, monitoring and control systems, manufacturing industry, medical technology, chemical / pharmaceutical industry, workshops, automotive.

"

### Tehnične Specifikacije

Min. sobna temperatura [°C]	-20
Min. temperatura medija [°C]	-20
Delovni tlak	0 to 35 bar, maximum static working pressure (non-pulsating)
Merjenje pretoka	at 6 bar and $\Delta p = 0.5$ bar
Ohišje	Brass with a bare metal surface
Povezava	Hose connection 8x6
Pritrdilni obroč	Stainless steel
Različica	Swivelling 360°
Rokav	Brass with a bare metal surface
Telo ventila	Brass with a bare metal surface
Tesnilo	NBR
Vzmet	Stainless steel
Zaporni zatič	Stainless steel
DN	7.2
a/f [mm]	22
Max. sobna temperatura [°C]	100
Max. temperatura medija [°C]	100
Dolžina [mm]	132.0
Pretok	1000 l/min (air)