

Datum: 12.06.2026

Hitre spojke I.D. 7.2 ponikljana medenina, G 1/4 notranji navoj

Kategorija: [Quick disconnect coupling DN 7.2, female](#)
Šifra: **107283RIE**

(slika je simbolična)

Kratek opis

Quick-connect coupling I.D. 7.2, nickel-plated brass, G 1/4 IT, Operating pressure 0 - 35 bar, Temp. -20 °C to 100 °C

Universal, one-hand quick disconnect couplings, one side sealing, suitable for a wide range of tasks and applications! The closed sleeve protects the coupling from dirt.

To prevent injuries or a "whiplash" effect, we recommend that the plug-in nipple is held with one hand during uncoupling.

These quick disconnect couplings are not suitable for direct attachment to pulsating tools.

We recommend using our vibration dampers, according to ISO 6150 § 7.1.

Areas of application: Pneumatic system, machine and plant engineering, measurement, monitoring and control systems, manufacturing industry, medical technology, chemical / pharmaceutical industry, workshops, automotive.

Tehnične Specifikacije

Min. sobna temperatura [°C]	-20
Min. temperatura medija [°C]	-20
Delovni tlak	0 to 35 bar, maximum static working pressure (non-pulsating)
Merjenje pretoka	at 6 bar and $\Delta p = 0.5$ bar
Ohišje	Nickel-plated brass
Povezava	G 1/4 IT
Pritrdilni obroč	Stainless steel 1.4310
Rokav	Nickel-plated brass
Telo ventila	Brass with a bare metal surface
Tesnilo	NBR
Vzmet	Stainless steel 1.4310
Zaporni zatič	Stainless steel 1.4034
DN	7.2
a/f [mm]	22
Dolžina [mm]	41.0
Max. sobna temperatura [°C]	100
Max. temperatura medija [°C]	100
Pretok	1000 l/min (air)