

Datum: 31.05.2026



(slika je simbolična)

## Hitre spojke I.D. 7.2 »connect line«, G 3/8 notranji navoj

Kategorija: [Quick disconnect coupling DN 7.2, female](#)  
Šifra: **115633RIE**

### Kratek opis

Quick-connect coupling I.D. 7.2 »connect line«, nickel-plated brass, G 3/8 IT, Operating pressure 0 - 35 bar, Temp. -20°C to 100°C

Universal, one-hand quick disconnect couplings, one side sealing, at an unbeatably low price.

The closed sleeve protects the coupling from dirt.

In combination with steel plugs, this coupling can also be used for pneumatic tools thanks to its hardened locking pins.

To prevent injuries or a "whiplash" effect, we recommend that the plug-in nipple is held with one hand during uncoupling.

These quick disconnect couplings are not suitable for direct attachment to pulsating tools.

We recommend using our vibration dampers, according to ISO 6150 § 7.1.

Areas of application: Pneumatic system, machine and plant engineering, measurement, monitoring and control systems, manufacturing industry, medical technology, chemical / pharmaceutical industry, workshops, automotive.

### Tehnične Specifikacije

Min. sobna temperatura [°C]	-20
Min. temperatura medija [°C]	-20
Delovni tlak	0 to 35 bar, maximum static working pressure (non-pulsating) at 6 bar and $\Delta p = 0.5$ bar
Merjenje pretoka	Nickel-plated brass
Ohišje	G 3/8 IT
Povezava	Stainless steel
Pritrdilni obroč	Nickel-plated brass
Rokav	Nickel-plated brass
Telo ventila	NBR
Tesnilo	Stainless steel
Vzmet	Stainless steel
Zaporni zatič	7.2
DN	21
a/f [mm]	40.5
Dolžina [mm]	100
Max. sobna temperatura [°C]	100
Max. temperatura medija [°C]	100
Pretok	1000 l/min (air)