

Datum: 13.03.2026

Davčna št.: SI 56119488  
Telefon: 01 500 14 42  
E-mail: [info@podjetje-trg.si](mailto:info@podjetje-trg.si)  
WWW: [www.karcher-trg.si](http://www.karcher-trg.si)

(slika je simbolična)

## [Hitre spojke I.D. 7.6, pocinkano /medenina, R 3/8 zunanji navoj](#)

Kategorija: [Quick disconnect coupling DN 7.6, male](#)  
Šifra: **107357RIE**

### Kratek opis

Quick-connect coupling I.D. 7.6, galvanised steel / brass, R 3/8 ET, Operating pressure max. 16 bar, Temp. -20 °C to 100 °C

High-quality, one-hand quick disconnect couplings made of brass / steel for high flow rates.

Specially designed for all applications susceptible to severe mechanical wear.

Strong, impact and vibration-resistant design for demanding environments.

The stream line type has an integrated hose stem.

### Tehnične Specifikacije

Min. sobna temperatura [°C]	-20
Min. temperatura medija [°C]	-20
Merjenje pretoka	at 6 bar and $\Delta_p = 0.5$ bar
Ohišje	Steel
Povezava	R 3/8 ET
Rokav	Hardened and nickel-plated steel
Tesnilo	NBR
Vzmet	Stainless steel
DN	7.6
Max. obratovalni tlak [bar]	16
a/f [mm]	20
Dolžina [mm]	61.0
Max. sobna temperatura [°C]	100
Max. temperatura medija [°C]	100
Pretok	2100 l/min (air)