



(slika je simbolična)

## Hitre spojke I.D. 7.6 »stream line«, pocinkano /Medenina

Kategorija: [Quick disconnect coupling DN 7.6, »stream line«](#)  
Šifra: **107368RIE**

### Kratek opis

Quick-connect coupling I.D. 7.6, »stream line«, galvanised steel / brass, for hose 12x8, Operating pressure max. 16 bar  
High-quality, one-hand quick disconnect couplings made of brass / steel for high flow rates.  
Specially designed for all applications susceptible to severe mechanical wear.  
Strong, impact and vibration-resistant design for demanding environments.  
The stream line type has an integrated hose stem.

### Tehnične Specifikacije

Min. sobna temperatura [°C]	-20
Min. temperatura medija [°C]	-20
Merjenje pretoka	at 6 bar and $\Delta_p = 0.5$ bar
Ohišje	Steel
Rokav	Hardened and nickel-plated steel
Tesnilo	NBR
Vzmet	Stainless steel
DN	7.6
Za cevi [mm]	12x8
Max. obratovalni tlak [bar]	16
a/f 1 [mm]	19
a/f 2 [mm]	20
Dolžina [mm]	68.0
Max. sobna temperatura [°C]	100
Max. temperatura medija [°C]	100
Pretok	2100 l/min (air)