

Datum: 02.07.2026



(slika je simbolična)

## Hitre spojke z Z.N. I.D. 2.7iz med.G 1/8 Z.N.

Kategorija: [Quick disconnect coupling DN 2.7, male](#)  
Šifra: **10707ORIE**

### Kratek opis

Quick-connect coupling I.D. 2.7, bright brass, G 1/8 ET,  
Operating pressure 0 - 35 bar, Med. / ambient temp. -20°C  
to 100°C

"

One-hand quick disconnect couplings, one side sealing,  
extremely compact with a large bore and only a small  
pressure drop.

To prevent injuries or a "whiplash" effect, we recommend  
that the plug-in nipple is held with one hand during  
uncoupling.

Areas of application: Pneumatic system, machine and plant  
engineering, measurement, monitoring and control systems,  
manufacturing industry, medical technology, chemical /  
pharmaceutical industry, automotive.

"

### Tehnične Specifikacije

|                              |  |
|------------------------------|--|
| Min. sobna temperatura [°C]  | -20  |
| Min. temperatura medija [°C] | -20  |
| Delovni tlak                 | 0 to 35 bar, maximum static working pressure (non-pulsating) |
| Krogla                       | Stainless steel  |
| Merjenje pretoka             | at 6 bar and $\Delta p = 0.5$ bar                            |
| Ohišje                       | Brass with a bare metal surface                              |
| Povezava                     | G 1/8 ET   |
| Pritrdilni obroč             | Stainless steel  |
| Rokav                        | Brass with a bare metal surface                              |
| Telo ventila                 | Brass with a bare metal surface                              |
| Tesnilo                      | NBR  |
| Vzmet                        | Stainless steel  |
| DN                           | 2.7  |
| a/f [mm]                     | 11   |
| Dolžina [mm]                 | 28.0   |
| Max. sobna temperatura [°C]  | 100  |
| Max. temperatura medija [°C] | 100  |
| Pretok                       | 165 l/min (air)  |