

Datum: 05.06.2026



In-line Tlačni reg.2 x IT, G 1/4, AF 17, prednast. na 1 bar

Kategorija: [Inline pressure regulators, 2 x IT, non-self-rel.](#)Šifra: **101494RIE**

(slika je simbolična)

Kratek opis

Inline pressure regulator, 2 x IT, without secondary venting, G 1/4, AF 17, Working pressure (pre-set) 1 bar, PN max. 18 bar

This single-acting diaphragm regulator can be installed in any pneumatic system. Since the pressure is preset in the factory and cannot be altered, the product is also tamper-proof.

We recommend mounting the regulator directly on the tool to make sure the correct pressure is applied. In this case, the tool is never stressed by the higher pressure of the supply system and is protected against pressure fluctuations in hoses, pipes, etc.

Energy efficiency and economic efficiency can be achieved by using an inline pressure regulator.

Tehnične Specifikacije

Merjenje pretoka	At P1 = 12 bar and pressure drop $\Delta p = 0.5$ bar
Navoj	G 1/4
Notranji deli	G 1/4
Ohišje	Zinc
Serijska	inline
Delovni tlak (prednastavitev) [bar]	1
a/f [mm]	17
Max. obratovalni tlak [bar]	18
A [mm]	34.0
B [mm]	52.0
Max. temperaturno območje [°C]	60
Pretok [l/min]	400