



Datum: 04.11.2025

Davčna št.: SI 56119488 Telefon: 01 500 14 42 E-mail: info@podietie-trg.si

E-mail: info@podjetje-trg.si **WWW:** www.www.karcher-trg.si



In-line tlačni regulator, IT/ET, G 1/4, prednastavljen na 2 bar

Kategorija: Inline pressure regulator, IT/ET, self-relieving

Šifra: **101488RIE**

(slika je simbolična)

Kratek opis

Inline pressure regulator, IT/ET, with secondary venting, Prepressure dependent, G 1/4, Working pressure (pre-set) 2 bar The majority of pneumatic tools are connected directly to the compressed air supply by means of a quick disconnect coupling, in other words they tend to be supplied with a higher pressure than is actually required. Which increases consumption and leads to tool overload. Added safety is provided by the automatic self-relieving function. If the tool is disconnected from the hose, it continues to work for a short period, even though it has been switched off, owing to the residual pressure that is present on the tool side. Inadvertent operation of the tool can thus lead to serious injuries to the user (tackers or nail drivers can fire up to another ten shots). This effect can be prevented by using the inline pressure regulators, which have a preset pressure determined by the application, thereby achieving energy efficiency and economy.

Tehnične Specifikacije

Navoj	G 1/4
Notranji deli	Stainless steel, nitrile rubber, brass
Ohišje	Aluminium
Serija	inline
Delovni tlak (prednastavitev)	2
[bar]	2
a/f 1 [mm]	16
a/f 2 [mm]	19
Max. obratovalni tlak [bar]	25
A [mm]	69.0
Max. temperaturno območje [°C]	80
Pretok [l/min]	500