



(slika je simbolična)

Javl. Kon. položaja tip M2 with mikro stikalo,4 V DC-250 V AC

Kategorija: [End position feedback, with microswitch](#)
Šifra: **103688RIE**

Kratek opis

End position feedback type M 2 with micro-switch, 4 V DC - 250 V AC, Changeover contact, 1 mA - 5 mA, IP 67, Temp. -20°C to 70°C

Robust type in a plastic housing

- Universal indicator for NAMUR sizes 80 x 30 and 130 x 30
- Height-adjustable feet that adapt to different pinion projections
- ON / OFF position indicator also visible from a distance
- Easy-to-adjust, self-locking trip cam

Tehnične Specifikacije

Min. temperaturno območje [°C]	-20
Glava	Polycarbonate, transparent
Gred	Polyamide PA6, black
IP zaščita	IP 67, acc. to DIN EN 60529
Kabelska uvodnica	M20x1.5
Montažni most	PA6 with 30 % glass fibre
Ohišje	Polyamide blue or black
Opis	End position feedback, M 2 type with microswitch
Preklopna funkcija	Changeover, silver-plated contacts
Različica	with microswitch
Tesnilo	EPDM and NBR
Vijaki	Stainless steel 1.4301
Minimalna preklopna zmogljivost	1 mA at 4 V DC
Nominalna preklopna zmogljivost	1 mA to 5 A at 250 V AC
Max. temperaturno območje [°C]	70