



(slika je simbolična)

## Javl.končneg položaja tip D 2, induktiven senzor, 3-wire PNP

Kategorija: [End position feedback with inductive sensors](#)  
Šifra: **103689RIE**

### Kratek opis

End position feedback type D 2, inductive sensors, 3-wire PNP, plus switched, 10 V-30 V DC, 100 mA, IP 67, Temp. -20°C to 70°C  
Robust type in a plastic housing  
- Universal indicator for NAMUR sizes 80 x 30 and 130 x 30  
- Height-adjustable feet that adapt to different pinion projections  
- ON / OFF position indicator also visible from a distance  
- Easy-to-adjust, self-locking trip cam

### Tehnične Specifikacije

Min. temperaturno območje [°C]	-20
Glava	Polycarbonate, transparent
Gred	Polyamide PA6, black
IP zaščita	IP 67, acc. to DIN EN 60529
Kabelska uvodnica	M20x1.5
Montažni most	PA6 with 30 % glass fibre
Ohišje	Polyamide blue or black
Opis	End position feedback, D 2 type with inductive 3-wire sensors
Preklopna funkcija	Positive switching, PNP NO contact, damped or undamped in the end position
Različica	with inductive sensors, 3-wire PNP
Tesnilo	EPDM and NBR
Vijaki	Stainless steel 1.4301
Območje napetosti	10 V - 30 V/DC
Max. temperaturno območje [°C]	70
Obratovalni tok	100 mA