


Datum: 12.06.2026

Davčna št.: SI 56119488
Telefon: 01 500 14 42
E-mail: info@podjetje-trg.si
WWW: www.karcher-trg.si



Kaljeni cevni vtikač DN 9, zunanji navoj, G 1/4, dolžina 15

Kategorija: [Push-in plug DN 9, without shut-off valve, ET](#)
Šifra: **107978RIE**

(slika je simbolična)

Kratek opis

Tempered plug-in nipple DN 9, Exterior thread, nickel-plated brass, G 1/4, Operating pressure max. 15 bar, Temp. -20 °C to 160 °C

Compatible with HASCO Z 8 system.

For temperature control applications involving hot or cold water or heat transfer oil.

Optionally with free passage, one or both sides sealing.

Female-threaded couplings and plugs with female-threaded PTFE seal.

Tehnične Specifikacije

Min. sobna temperatura [°C]	-20
Min. temperatura medija [°C]	-20
Krogla	Stainless steel
Material	Nickel-plated brass
Navoj	G 1/4
Pritrdilni obroč	Stainless steel
Srednje	Air, water, oil, vacuum
Tesnilo	FPM (PTFE coated)
Vzmet	Stainless steel
a/f [mm]	15
Max. obratovalni tlak [bar]	15
Dolžina [mm]	26.0
Max. sobna temperatura [°C]	160
Max. temperatura medija [°C]	160