

Datum: 14.06.2026

Davčna št.: SI 56119488
Telefon: 01 500 14 42
E-mail: info@podjetje-trg.si
WWW: www.karcher-trg.si



(slika je simbolična)

Kaljeni vložek DN 9, Medenina, cevni priklop 13 mm

Kategorija: [Push-in hose stem DN 9, without shut-off valve](#)
Šifra: **107974RIE**

Kratek opis

Tempered plug-on connector DN 9, Brass 2.0401, Hose connection 13 mm, Operating pressure max. 15 bar, Temp. -20 °C to 160 °C
Compatible with HASCO Z 8 system.
For temperature control applications involving hot or cold water or heat transfer oil.
Optionally with free passage, one or both sides sealing.
Female-threaded couplings and plugs with female-threaded PTFE seal.

Tehnične Specifikacije

| | |
|------------------------------|-------------------------|
| Min. sobna temperatura [°C] | -20 |
| Min. temperatura medija [°C] | -20 |
| Krogla | Stainless steel |
| Material | Brass 2.0401 |
| Pritrdilni obroč | Stainless steel |
| Srednje | Air, water, oil, vacuum |
| Tesnilo | FPM (PTFE coated) |
| Vzmet | Stainless steel |
| Priključek za cev [mm] | 13 |
| Max. obratovalni tlak [bar] | 15 |
| Dolžina [mm] | 42.0 |
| Max. sobna temperatura [°C] | 160 |
| Max. temperatura medija [°C] | 160 |