

Datum: 13.04.2026

Davčna št.: SI 56119488  
Telefon: 01 500 14 42  
E-mail: [info@podjetje-trg.si](mailto:info@podjetje-trg.si)  
WWW: [www.karcher-trg.si](http://www.karcher-trg.si)



(slika je simbolična)

## Kaljeni vložek DN 9, Medenina, cevni priklop 13 mm

Kategorija: [Push-in hose stem DN 9, without shut-off valve](#)  
Šifra: **107974RIE**

### Kratek opis

Tempered plug-on connector DN 9, Brass 2.0401, Hose connection 13 mm, Operating pressure max. 15 bar, Temp. -20 °C to 160 °C  
Compatible with HASCO Z 8 system.  
For temperature control applications involving hot or cold water or heat transfer oil.  
Optionally with free passage, one or both sides sealing.  
Female-threaded couplings and plugs with female-threaded PTFE seal.

### Tehnične Specifikacije

Min. sobna temperatura [°C]	-20
Min. temperatura medija [°C]	-20
Krogla	Stainless steel
Material	Brass 2.0401
Pritrdilni obroč	Stainless steel
Srednje	Air, water, oil, vacuum
Tesnilo	FPM (PTFE coated)
Vzmet	Stainless steel
Priključek za cev [mm]	13
Max. obratovalni tlak [bar]	15
Dolžina [mm]	42.0
Max. sobna temperatura [°C]	160
Max. temperatura medija [°C]	160