TRG d.o.o.
Celovška cesta 150, 1000 Ljubljana

Davčna št.: SI 56119488
Telefon: 01 500 14 42
E-mail: info@podjetje-trg.si
WWW: www.www.karcher-trg.si

Datum: 16.11.2026



(slika je simbolična)

Kamlok hitra spojka,thread, A tip, Alu, G 2

Kategorija: Kamlok male adapter, female threaded, Part A
Šifra: **108070RIE**

Kratek opis

Kamlok quick-connect plug with interior thread, A type, Aluminium, G 2, Plug Ø 63 mm, Pressure max. 16 bar, Temp. max. 68 °C
Coupling system for quick and easy connection of two hoses or for joining one hose to a machine connection.
A male part and a female part are joined together by shifting the handles.
There is no need to turn the hose!
Kamlok couplings are used for a wide range of applications in industrial plant and mechanical engineering, tank and container construction, the chemical industry, food processing, mining, refuelling systems, defence technology, etc.

Tehnične Specifikacije

Min. temperaturno območje [°C]	-20
Navoj	G 2
Tesnilo	NBR, resistant to oils and benzine
Max. obratovalni tlak [bar]	16
L [mm]	59.0
Vtič Ø [mm]	63
Max. temperaturno območje [°C]	68