

Datum: 05.06.2026

Davčna št.: SI 56119488
Telefon: 01 500 14 42
E-mail: info@podjetje-trg.si
WWW: www.karcher-trg.si



(slika je simbolična)

Kamlok hitra spojka, thread, A tip, Alu, G 3/4

Kategorija: [Kamlok male adapter, female threaded, Part A](#)
Šifra: **108066RIE**

Kratek opis

Kamlok quick-connect plug with interior thread, A type, Aluminium, G 3/4, Plug Ø 32 mm, Pressure max. 16 bar, Temp. max. 68 °C

Coupling system for quick and easy connection of two hoses or for joining one hose to a machine connection.

A male part and a female part are joined together by shifting the handles.

There is no need to turn the hose!

Kamlok couplings are used for a wide range of applications in industrial plant and mechanical engineering, tank and container construction, the chemical industry, food processing, mining, refuelling systems, defence technology, etc.

Tehnične Specifikacije

| | |
|--------------------------------|------------------------------------|
| Min. temperaturno območje [°C] | -20 |
| Navoj | G 3/4 |
| Tesnilo | NBR, resistant to oils and benzine |
| Max. obratovalni tlak [bar] | 16 |
| Vtič Ø [mm] | 32 |
| L [mm] | 41.0 |
| Max. temperaturno območje [°C] | 68 |