**TRG d.o.o.**
**Celovška cesta 150, 1000 Ljubljana**

**Davčna št.:** SI 56119488
**Telefon:** 01 500 14 42
**E-mail:** info@podjetje-trg.si
**WWW:** www.www.karcher-trg.si

**Datum:** 16.11.2026



(slika je simbolična)

# Kamlok hitra spojka,thread, A tip, Alu, G 3/4

Kategorija: Kamlok male adapter, female threaded, Part A
Šifra: **108066RIE**

## Kratek opis

Kamlok quick-connect plug with interior thread, A type, Aluminium, G 3/4, Plug Ø 32 mm, Pressure max. 16 bar, Temp. max. 68 °C
Coupling system for quick and easy connection of two hoses or for joining one hose to a machine connection.
A male part and a female part are joined together by shifting the handles.
There is no need to turn the hose!
Kamlok couplings are used for a wide range of applications in industrial plant and mechanical engineering, tank and container construction, the chemical industry, food processing, mining, refuelling systems, defence technology, etc.

## Tehnične Specifikacije

| | |
|---|---|
| Min. temperaturno območje [°C] | -20 |
| Navoj | G 3/4 |
| Tesnilo | NBR, resistant to oils and benzine |
| Max. obratovalni tlak [bar] | 16 |
| Vtič Ø [mm] | 32 |
| L [mm] | 41.0 |
| Max. temperaturno območje [°C] | 68 |