

Datum: 04.04.2026

Davčna št.: SI 56119488  
Telefon: 01 500 14 42  
E-mail: [info@podjetje-trg.si](mailto:info@podjetje-trg.si)  
WWW: [www.karcher-trg.si](http://www.karcher-trg.si)



(slika je simbolična)

## Kamlok hitra spojka,thread, A tip, Alu, G 3

Kategorija: [Kamlok male adapter, female threaded, Part A](#)  
Šifra: **108072RIE**

### Kratek opis

Kamlok quick-connect plug with interior thread, A type, Aluminium, G 3, Plug Ø 92 mm, Pressure max. 16 bar, Temp. max. 68 °C  
Coupling system for quick and easy connection of two hoses or for joining one hose to a machine connection.  
A male part and a female part are joined together by shifting the handles.  
There is no need to turn the hose!  
Kamlok couplings are used for a wide range of applications in industrial plant and mechanical engineering, tank and container construction, the chemical industry, food processing, mining, refuelling systems, defence technology, etc.

### Tehnične Specifikacije

|                                |                                    |
|--------------------------------|------------------------------------|
| Min. temperaturno območje [°C] | -20                                |
| Navoj                          | G 3                                |
| Tesnilo                        | NBR, resistant to oils and benzine |
| Max. obratovalni tlak [bar]    | 16                                 |
| Max. temperaturno območje [°C] | 68                                 |
| L [mm]                         | 71.7                               |
| Vtič Ø [mm]                    | 92                                 |