TRG d.o.o.
Celovška cesta 150, 1000 Ljubljana

Davčna št.: SI 56119488
Telefon: 01 500 14 42
E-mail: info@podjetje-trg.si
WWW: www.www.karcher-trg.si

Datum: 27.11.2026



(slika je simbolična)

Kamlok hitra spojka, zunanji navoj, F tip, 1.4401, R 3

Kategorija: Kamlok male adapter, male threaded, Part F
Šifra: **108137RIE**

Kratek opis

Kamlok quick-connect plug with exterior thread, F type, Stainless steel 1.4401, R 3, Plug Ø 92 mm, Pressure max. 16 bar
High-quality, robust, universal coupling system with a safety clamp for quick and easy connection of two hoses or for joining one hose to a machine connection.
A male part and a female part are joined together by shifting the handles.
There is no need to turn the hose!
Kamlok stainless steel couplings are designed for use with corrosive media in the chemical and petrochemical industries, steelmaking, shipbuilding, agriculture, etc.

Tehnične Specifikacije

Min. temperaturno območje [°C]	-20
Navoj	R 3
Tesnilo	NBR, resistant to oils and benzine
Max. obratovalni tlak [bar]	16
L [mm]	91.0
Vtič Ø [mm]	92
Max. temperaturno območje [°C]	95