

Datum: 21.04.2026

Davčna št.: SI 56119488  
Telefon: 01 500 14 42  
E-mail: [info@podjetje-trg.si](mailto:info@podjetje-trg.si)  
WWW: [www.karcher-trg.si](http://www.karcher-trg.si)



## Kamlok hitra spojka, zunanji navoj, F tip, Alu, R 1 1/4

Kategorija: [Kamlok male adapter, male threaded, Part F](#)  
Šifra: **108060RIE**

(slika je simbolična)

### Kratek opis

Kamlok quick-connect plug with exterior thread, F type, Aluminium, R 1 1/4, Plug Ø 45 mm, Pressure max. 16 bar, Temp. max. 68 °C

Coupling system for quick and easy connection of two hoses or for joining one hose to a machine connection.

A male part and a female part are joined together by shifting the handles.

There is no need to turn the hose!

Kamlok couplings are used for a wide range of applications in industrial plant and mechanical engineering, tank and container construction, the chemical industry, food processing, mining, refuelling systems, defence technology, etc.

### Tehnične Specifikacije

Min. temperaturno območje [°C]	-20
Navoj	R 1 1/4
Tesnilo	NBR, resistant to oils and benzine
Max. obratovalni tlak [bar]	16
Vtič Ø [mm]	45
Max. temperaturno območje [°C]	68
L [mm]	78.0