

Datum: 21.06.2026

Davčna št.: SI 56119488
Telefon: 01 500 14 42
E-mail: info@podjetje-trg.si
WWW: www.karcher-trg.si



(slika je simbolična)

[Kamlok hitra spojka, zunanji navoj, F tip, Alu, R 1 1/4](#)

Kategorija: [Kamlok male adapter, male threaded, Part F](#)
Šifra: **108060RIE**

Kratek opis

Kamlok quick-connect plug with exterior thread, F type, Aluminium, R 1 1/4, Plug Ø 45 mm, Pressure max. 16 bar, Temp. max. 68 °C

Coupling system for quick and easy connection of two hoses or for joining one hose to a machine connection.

A male part and a female part are joined together by shifting the handles.

There is no need to turn the hose!

Kamlok couplings are used for a wide range of applications in industrial plant and mechanical engineering, tank and container construction, the chemical industry, food processing, mining, refuelling systems, defence technology, etc.

Tehnične Specifikacije

Min. temperaturno območje [°C]	-20
Navoj	R 1 1/4
Tesnilo	NBR, resistant to oils and benzine
Max. obratovalni tlak [bar]	16
Vtič Ø [mm]	45
Max. temperaturno območje [°C]	68
L [mm]	78.0