TRG d.o.o.
Celovška cesta 150, 1000 Ljubljana

Davčna št.: SI 56119488
Telefon: 01 500 14 42
E-mail: info@podjetje-trg.si
WWW: www.www.karcher-trg.si

Datum: 14.11.2026



(slika je simbolična)

Kamlok tesnilni pokrov plugDP tipAluminijVel. 2Plug Ø 63

Kategorija: Kamlok male dust plug, Part DP
Šifra: **108086RIE**

Kratek opis

Kamlok cap plug, DP type, Aluminium, Size 2, Plug Ø 63 mm, Operating pressure max. 16 bar, Temp. max. 68 °C
Coupling system for quick and easy connection of two hoses or for joining one hose to a machine connection.
A male part and a female part are joined together by shifting the handles.
There is no need to turn the hose!
Kamlok couplings are used for a wide range of applications in industrial plant and mechanical engineering, tank and container construction, the chemical industry, food processing, mining, refuelling systems, defence technology, etc.

Tehnične Specifikacije

Min. temperaturno območje [°C]	-20
Tesnilo	NBR, resistant to oils and benzine
Velikost	2
Max. obratovalni tlak [bar]	16
A [mm]	63.0
Vtič Ø [mm]	63
C [mm]	63.5
Max. temperaturno območje [°C]	68