

Datum: 31.05.2026

Davčna št.: SI 56119488
Telefon: 01 500 14 42
E-mail: info@podjetje-trg.si
WWW: www.karcher-trg.si

(slika je simbolična)

Komp. cilind. del. v dveh smereh, bat Ø 100hod 5G 1/4

Kategorija: [Compact cylinder, double-acting, with magnet](#)
Šifra: **115241RIE**

Kratek opis

Compact cylinder »ACP«, double-acting, Piston Ø 100, Stroke 5, Connection G 1/4, Working pressure 1-10 bar, Temp. -20 °C to 70 °C
Characterised by a very short and compact design.
Suitable for filtered, unlubricated or lubricated compressed air.
If lubrication is used, it must be continuous.

Tehnične Specifikacije

Min. temperaturno območje [°C]	-20
Bat	Aluminium
Batnica	Steel
Batnica IT	M12x1.75
Ffunkcija	double-acting
Gewinde Kolbenstange	female piston rod with magnet
Magnet	Aluminium
Ovoj	G 1/4
Povezava	ACP series
Serija	NBR
Tesnilo	1
Min. delovni tlak [bar]	5
Stroke [mm]	10
Max. delovni tlak [bar]	25
Batnica Ø [mm]	70
Max. temperaturno območje [°C]	100
Bat Ø [mm]	