

Datum: 12.05.2026



Komp. cilind. del. v dveh smereh, bat Ø 12 hod 5,M5,ISO21287

Kategorija: [Compact cylinders double-acting, male piston rod](#)
Šifra: **155566RIE**

(slika je simbolična)

Kratek opis

Compact cyl.ISO 21287, double-acting, male piston rod magnet, PistonØ12, Stroke5, M5, Work.press.max.10bar, Temp.-20°C to 70°C
Series acc. to ISO 21287 characterised by a very short and compact design.
The standard type features a magnetic piston.
Piston rod optionally with male or female thread.
Suitable for filtered, unlubricated or lubricated compressed air.
If lubrication is used, it must be continuous.

Tehnične Specifikacije

Min. temperaturno območje [°C]	-20
Bat	Aluminium
Batnica	S45C steel, hard chrome-plated
ET batnice	M5x0.8
Ffunkcija	double-acting
Gewinde Kolbenstange	male piston rod with magnet
Magnet	Anodised aluminium jacket with T-slots
Ovoj	M5
Povezava	ACE series
Serija	acc. to ISO 21287
Standard	NBR
Tesnilo	5
Stroke [mm]	10
Max. delovni tlak [bar]	12
Bat Ø [mm]	70
Max. temperaturno območje [°C]	