

Datum: 31.05.2026

Davčna št.: SI 56119488
Telefon: 01 500 14 42
E-mail: info@podjetje-trg.si
WWW: www.karcher-trg.si

(slika je simbolična)

Komp. cilind. del. v dveh smereh, bat Ø 12hod 45M5x0,8

Kategorija: [Compact cylinder, double-acting, with magnet](#)
Šifra: **115269RIE**

Kratek opis

Compact cylinder »ACP«, double-acting, Piston Ø 12, Stroke 45, Connection M5x0,8, Working pressure 1-10 bar, Temp. -20 °C to 70 °C

Characterised by a very short and compact design.

Suitable for filtered, unlubricated or lubricated compressed air.

If lubrication is used, it must be continuous.

Tehnične Specifikacije

Min. temperaturno območje [°C]	-20
Bat	Aluminium
Batnica	Stainless steel 1.1191
Batnica IT	M3x0.5
Ffunkcija	double-acting
Gewinde Kolbenstange	female piston rod
Magnet	with magnet
Ovoj	Aluminium
Povezava	M5x0.8
Serija	ACP series
Tesnilo	NBR
Min. delovni tlak [bar]	1
Batnica Ø [mm]	6
Max. delovni tlak [bar]	10
Bat Ø [mm]	12
Stroke [mm]	45
Max. temperaturno območje [°C]	70