



(slika je simbolična)

Komp. cilind. del. v dveh smereh, bat Ø 50hod 35G 1/8

Kategorija: [Compact cylinder, double-acting, with magnet](#)
Šifra: **115363RIE**

Kratek opis

Compact cylinder »ACP«, double-acting, Piston Ø 50, Stroke 35, Connection G 1/8, Working pressure 1-10 bar, Temp. -20 °C to 70 °C

Characterised by a very short and compact design.

Suitable for filtered, unlubricated or lubricated compressed air.

If lubrication is used, it must be continuous.

Tehnične Specifikacije

| | |
|--------------------------------|-------------------------------|
| Min. temperaturno območje [°C] | -20 |
| Bat | Aluminium |
| Batnica | Steel |
| Batnica IT | M8x1.25 |
| Ffunkcija | double-acting |
| Gewinde Kolbenstange | female piston rod with magnet |
| Magnet | Aluminium |
| Ovoj | G 1/8 |
| Povezava | ACP series |
| Serija | NBR |
| Tesnilo | 1 |
| Min. delovni tlak [bar] | 10 |
| Max. delovni tlak [bar] | 16 |
| Batnica Ø [mm] | 35 |
| Stroke [mm] | 50 |
| Bat Ø [mm] | 70 |
| Max. temperaturno območje [°C] | |