

Datum: 02.07.2026

(slika je simbolična)

Komp. cilind. del. v dveh smereh, bat Ø 50hod 50G 1/8

Kategorija: [Metalwork](#)
Šifra: **106090RIE**

Kratek opis

Compact cylinder LINER, ISO 21287, double-acting, Piston Ø 50, Stroke 50, G 1/8, Working pressure max. 10 bar, Temp. -10°C to 60°C

New series acc. to ISO 21287 characterised by a very short and compact design.

The standard type features a magnetic piston.

Piston rod optionally with male or female thread.

Suitable for filtered, unlubricated or lubricated compressed air.

If lubrication is used, it must be continuous.

Tehnične Specifikacije

| | |
|--------------------------------|--|
| Min. temperaturno območje [°C] | -10 |
| Bat | POM |
| Batnica | C45 steel, hard chrome-plated |
| ET batnice | M12x1.25 |
| Ffunkcija | double-acting |
| Gewinde Kolbenstange | male piston rod |
| Magnet | with magnet |
| Ovoj | Anodised aluminium jacket with T-slots |
| Povezava | G 1/8 |
| Serija | LINER series |
| Standard | acc. to ISO 21287 |
| Tesnilo | NBR |
| Min. nastavljeni tlak [bar] | 0.4 |
| Max. delovni tlak [bar] | 10 |
| Bat Ø [mm] | 50 |
| Stroke [mm] | 50 |
| Max. temperaturno območje [°C] | 60 |