

Datum: 10.06.2026



## Komp. cilind. del. v dveh smereh, bat Ø40, hod 90, G1/8, ISO21287

Kategorija: [Compact cylinders double-acting, female piston rod](#)  
Šifra: **155421RIE**

(slika je simbolična)

### Kratek opis

Compact cyl. ISO 21287, double-acting, female piston rod, magnet, Piston Ø40, Stroke 90, G1/8, Work.press.max. 10bar, Temp. -20°C to 70°C  
Series acc. to ISO 21287 characterised by a very short and compact design.  
The standard type features a magnetic piston.  
Piston rod optionally with male or female thread.  
Suitable for filtered, unlubricated or lubricated compressed air.  
If lubrication is used, it must be continuous.

### Tehnične Specifikacije

Min. temperaturno območje [°C]	-20
Bat	Aluminium
Batnica	S45C steel, hard chrome-plated
Batnica IT	M8x1.25
Ffunkcija	double-acting
Gewinde Kolbenstange	female piston rod with magnet
Magnet	Anodised aluminium jacket with T-slots
Ovoj	G 1/8
Povezava	ACE series
Serija	acc. to ISO 21287
Standard	NBR
Tesnilo	10
Max. delovni tlak [bar]	40
Bat Ø [mm]	70
Max. temperaturno območje [°C]	90
Stroke [mm]	