

Datum: 26.04.2026



Komp. cilind. del. v dveh smereh, batØ50, hod20, G1/8, ISO21287

Kategorija: [Compact cylinders double-acting, female piston rod](#)
Šifra: **155433RIE**

(slika je simbolična)

Kratek opis

Compact cyl.ISO 21287, double-acting, female piston rod, magnet, PistonØ50, Stroke20, G1/8, Work.press.max.10bar, Temp.-20°C to 70°C
Series acc. to ISO 21287 characterised by a very short and compact design.
The standard type features a magnetic piston.
Piston rod optionally with male or female thread.
Suitable for filtered, unlubricated or lubricated compressed air.
If lubrication is used, it must be continuous.

Tehnične Specifikacije

| | |
|--------------------------------|--|
| Min. temperaturno območje [°C] | -20 |
| Bat | Aluminium |
| Batnica | S45C steel, hard chrome-plated |
| Batnica IT | M10x1.5 |
| Ffunkcija | double-acting |
| Gewinde Kolbenstange | female piston rod with magnet |
| Magnet | Anodised aluminium jacket with T-slots |
| Ovoj | G 1/8 |
| Povezava | ACE series |
| Serija | acc. to ISO 21287 |
| Standard | NBR |
| Tesnilo | 10 |
| Max. delovni tlak [bar] | 20 |
| Stroke [mm] | 50 |
| Bat Ø [mm] | 70 |
| Max. temperaturno območje [°C] | |