

**Datum:** 10.06.2026

## **Komp. cilind. del. v dveh smereh, batØ63, hod125, G1/8, ISO21287**

Kategorija: [Compact cylinders double-acting, female piston rod](#)  
Šifra: **155475RIE**

(slika je simbolična)

### **Kratek opis**

Compact cyl.ISO 21287, double-acting, female piston rod, magnet, PistonØ63, Stroke125, G1/8, Work.press.max.10bar, Temp.-20°C to 70°C  
Series acc. to ISO 21287 characterised by a very short and compact design.  
The standard type features a magnetic piston.  
Piston rod optionally with male or female thread.  
Suitable for filtered, unlubricated or lubricated compressed air.  
If lubrication is used, it must be continuous.

### **Tehnične Specifikacije**

Min. temperaturno območje [°C]	-20
Bat	Aluminium
Batnica	S45C steel, hard chrome-plated
Batnica IT	M10x1.5
Ffunkcija	double-acting
Gewinde Kolbenstange	female piston rod with magnet
Magnet	Anodised aluminium jacket with T-slots
Ovoj	G 1/8
Povezava	ACE series
Serija	acc. to ISO 21287
Standard	NBR
Tesnilo	10
Max. delovni tlak [bar]	63
Bat Ø [mm]	70
Max. temperaturno območje [°C]	125
Stroke [mm]	