

Datum: 02.06.2026



(slika je simbolična)

## Komp. cilind. del. v dveh smereh, bat Ø 40hod 10G 1/8

Kategorija: [Metalwork](#)  
Šifra: **105996RIE**

### Kratek opis

Compact cylinder LINER, ISO 21287, double-acting, Piston Ø 40, Stroke 10, G 1/8, Working pressure max. 10 bar, Temp. -10°C to 60°C

New series acc. to ISO 21287 characterised by a very short and compact design.

The standard type features a magnetic piston.

Piston rod optionally with male or female thread.

Suitable for filtered, unlubricated or lubricated compressed air.

If lubrication is used, it must be continuous.

### Tehnične Specifikacije

Min. temperaturno območje [°C]	-10
Bat	POM
Batnica	C45 steel, hard chrome-plated
Batnica IT	M8
Ffunkcija	double-acting
Gewinde Kolbenstange	female piston rod with magnet
Magnet	Anodised aluminium jacket with T-slots
Ovoj	G 1/8
Povezava	LINER series
Serija	acc. to ISO 21287
Standard	NBR
Tesnilo	0.4
Min. nastavljeni tlak [bar]	10
Max. delovni tlak [bar]	10
Stroke [mm]	40
Bat Ø [mm]	60
Max. temperaturno območje [°C]	