

**Datum:** 12.05.2026

## Komp. cilind.del. v dveh smereh,bat Ø80,hod275,G1/8,ISO21287

Kategorija: [Compact cylinders double-acting, male piston rod](#)  
Šifra: **155754RIE**

(slika je simbolična)

### Kratek opis

Compact cyl.ISO 21287, double-acting, male piston rod magnet, PistonØ80, Stroke275, G1/8, Work.press.max.10bar, Temp.-20°C to 70°C Series acc. to ISO 21287 characterised by a very short and compact design.  
The standard type features a magnetic piston.  
Piston rod optionally with male or female thread.  
Suitable for filtered, unlubricated or lubricated compressed air.  
If lubrication is used, it must be continuous.

### Tehnične Specifikacije

Min. temperaturno območje [°C]	-20
Bat	Aluminium
Batnica	S45C steel, hard chrome-plated
ET batnice	M16x1.5
Ffunkcija	double-acting
Gewinde Kolbenstange	male piston rod
Magnet	with magnet
Ovoj	Anodised aluminium jacket with T-slots
Povezava	G 1/8
Serija	ACE series
Standard	acc. to ISO 21287
Tesnilo	NBR
Max. delovni tlak [bar]	10
Max. temperaturno območje [°C]	70
Bat Ø [mm]	80
Stroke [mm]	275