

Datum: 12.05.2026

Komp. cilind.del. v dveh smereh, batØ125, hod250, G1/4, ISO21287

Kategorija: [Compact cylinders double-acting, male piston rod](#)
Šifra: **155809RIE**

(slika je simbolična)

Kratek opis

Compact cyl.ISO 21287, double-acting, male piston rod magnet, PistonØ125,Stroke250, G1/4, Work.press.max.10bar, Temp.-20°C to 70°C Series acc. to ISO 21287 characterised by a very short and compact design.
The standard type features a magnetic piston.
Piston rod optionally with male or female thread.
Suitable for filtered, unlubricated or lubricated compressed air.
If lubrication is used, it must be continuous.

Tehnične Specifikacije

| | |
|--------------------------------|--|
| Min. temperaturno območje [°C] | -20 |
| Bat | Aluminium |
| Batnica | S45C steel, hard chrome-plated |
| ET batnice | M20x1.5 |
| Ffunkcija | double-acting |
| Gewinde Kolbenstange | male piston rod |
| Magnet | with magnet |
| Ovoj | Anodised aluminium jacket with T-slots |
| Povezava | G 1/4 |
| Serija | ACE series |
| Standard | acc. to ISO 21287 |
| Tesnilo | NBR |
| Max. delovni tlak [bar] | 10 |
| Max. temperaturno območje [°C] | 70 |
| Bat Ø [mm] | 125 |
| Stroke [mm] | 250 |