

Datum: 10.05.2026



(slika je simbolična)

[komp.cilinder,enosmerni,zunanjibat Ø16, hod 5, M5, ISO21287](#)

Kategorija: [Compact cylinders, single-acting, extended, female](#)
Šifra: **155908RIE**

Kratek opis

Compact cyl.ISO 21287, single-acting, female piston rod, ext.,magnet,PistonØ16,Stroke5,M5, Work.press.max.10bar,Temp.-20°C to 70°C Series acc. to ISO 21287 characterised by a very short and compact design.
The standard type features a magnetic piston.
Piston rod optionally with male or female thread.
Suitable for filtered, unlubricated or lubricated compressed air.
If lubrication is used, it must be continuous.

Tehnične Specifikacije

Min. temperaturno območje [°C]	-20
Bat	Aluminium
Batnica	S45C steel, hard chrome-plated
Batnica IT	M4x0.7
Ffunkcija	single-acting
Gewinde Kolbenstange	female piston rod with magnet
Magnet	Anodised aluminium jacket with T-slots
Ovoj	M5
Povezava	ATE series
Serija	acc. to ISO 21287
Standard	pressureless in the extended position
Starting position	NBR
Tesnilo	5
Stroke [mm]	10
Max. delovni tlak [bar]	16
Bat Ø [mm]	70
Max. temperaturno območje [°C]	