



(slika je simbolična)

[komp.cilinder,enosmerni,zunanjibat Ø16, hod 20, M5, ISO21287](#)

Kategorija: [Compact cylinders, single-acting, extended, male](#)
Šifra: **155958RIE**

Kratek opis

Compact cyl.ISO 21287, single-acting, male piston rod ext.,magnet,PistonØ16,Stroke20,M5, Work.press.max.10bar, Temp.-20°C to 70°C
Series acc. to ISO 21287 characterised by a very short and compact design.
The standard type features a magnetic piston.
Piston rod optionally with male or female thread.
Suitable for filtered, unlubricated or lubricated compressed air.
If lubrication is used, it must be continuous.

Tehnične Specifikacije

| | |
|--------------------------------|--|
| Min. temperaturno območje [°C] | -20 |
| Bat | Aluminium |
| Batnica | S45C steel, hard chrome-plated |
| ET batnice | M6x1.0 |
| Ffunkcija | single-acting |
| Gewinde Kolbenstange | male piston rod |
| Magnet | with magnet |
| Ovoj | Anodised aluminium jacket with T-slots |
| Povezava | M5 |
| Serija | ATE series |
| Standard | acc. to ISO 21287 |
| Starting position | pressureless in the extended position |
| Tesnilo | NBR |
| Max. delovni tlak [bar] | 10 |
| Bat Ø [mm] | 16 |
| Stroke [mm] | 20 |
| Max. temperaturno območje [°C] | 70 |