

Datum: 10.05.2026



(slika je simbolična)

## [komp.cilinder,enosmerni,zunanjibat Ø16, hod 25, M5, ISO21287](#)

Kategorija: [Compact cylinders, single-acting, extended, male](#)  
Šifra: **155959RIE**

### Kratek opis

Compact cyl.ISO 21287, single-acting, male piston rod ext.,magnet,PistonØ16,Stroke25,M5, Work.press.max.10bar, Temp.-20°C to 70°C

Series acc. to ISO 21287 characterised by a very short and compact design.

The standard type features a magnetic piston.

Piston rod optionally with male or female thread.

Suitable for filtered, unlubricated or lubricated compressed air.

If lubrication is used, it must be continuous.

### Tehnične Specifikacije

Min. temperaturno območje [°C]	-20
Bat	Aluminium
Batnica	S45C steel, hard chrome-plated
ET batnice	M6x1.0
Ffunkcija	single-acting
Gewinde Kolbenstange	male piston rod
Magnet	with magnet
Ovoj	Anodised aluminium jacket with T-slots
Povezava	M5
Serija	ATE series
Standard	acc. to ISO 21287
Starting position	pressureless in the extended position
Tesnilo	NBR
Max. delovni tlak [bar]	10
Bat Ø [mm]	16
Stroke [mm]	25
Max. temperaturno območje [°C]	70