

Datum: 01.07.2026



(slika je simbolična)

## [komp.cilinder,enosmerni,zunanjiP-Ø40, hod 20, G1/8, ISO21287](#)

Kategorija: [Compact cylinders, single-acting, extended, male](#)  
Šifra: **155978RIE**

### Kratek opis

Compact cyl.ISO 21287, single-acting, male piston rod ext.,magnet,PistonØ40,Stroke20,G1/8, Work.press.max.10bar,Temp.-20°C to 70°C Series acc. to ISO 21287 characterised by a very short and compact design.  
The standard type features a magnetic piston.  
Piston rod optionally with male or female thread.  
Suitable for filtered, unlubricated or lubricated compressed air.  
If lubrication is used, it must be continuous.

### Tehnične Specifikacije

Min. temperaturno območje [°C]	-20
Bat	Aluminium
Batnica	S45C steel, hard chrome-plated
ET batnice	M10x1.25
Ffunkcija	single-acting
Gewinde Kolbenstange	male piston rod
Magnet	with magnet
Ovoj	Anodised aluminium jacket with T-slots
Povezava	G 1/8
Serija	ATE series
Standard	acc. to ISO 21287
Starting position	pressureless in the extended position
Tesnilo	NBR
Max. delovni tlak [bar]	10
Stroke [mm]	20
Bat Ø [mm]	40
Max. temperaturno območje [°C]	70