TRG d.o.o.
Celovška cesta 150, 1000 Ljubljana

Davčna št.: SI 56119488
Telefon: 01 500 14 42
E-mail: info@podjetje-trg.si
WWW: www.www.karcher-trg.si

Datum: 17.11.2026



(slika je simbolična)

Kompakt.ejektor CP digi. vakum. stikalo, velikost šobe2 mm, NC

Kategorija: Compact ejector »CP«
Šifra: **108411RIE**

Kratek opis

Compact ejector »CP«, Digital vacuum switch, Nozzle size 2 mm, NC, Compressed air / vacuum conn. G 1/4 IT, G 3/8 IT, PN 5 - 6 bar
Purely pneumatic vacuum ejector that operates on the Venturi principle. Compressed air enters the ejector at A and flows through the nozzle B. This results in a vacuum immediately behind the nozzle outlet, and air is drawn in through the vacuum inlet D. This air and the driving air leave the ejector via the silencer C.
Properties:
• Vacuum generator with integrated control valves and system monitoring functions
• Gripping and blowing off can be controlled without the need for external valves
• Optimised air consumption thanks to many models with differing suction capacities
• Minimum energy costs in continuous operation thanks to automatic air-saving
• Easy adjustment with foil keypad and LED display of the settings
Applications:
Handling of air-tight or slightly porous workpieces in fully automated handling
systems, e.g. in the robotics, automotive, packaging, electronics, electrical
engineering and metalworking industries.

Tehnične Specifikacije

Dovod stisnjenega zraka	G 1/4 IT
Dovod vakuuma	G 3/8 IT
Integrirano	NC blow-off valve, filter, silencer, non-return valve
Položaj sesalnega ventila v mirovanju	NC
Telo	Anodised aluminium
Velikost šobe [mm]	2
Min. obratovalni tlak [bar]	5
Max. obratovalni tlak [bar]	6
Premer [mm]	22.0
Dolžina [mm]	113.0
Max. stopnja sesanja [l/min]	116
Višina [mm]	168.0
Poraba zraka med evakuacijo [l/min]	190
Teža [g]	465.0