

Datum: 21.09.2024



## Kompaktni cilindri, enosmerni, bat Ø 25, hod 25, M5, ISO21287

Kategorija: [Compact cylinders single-acting, retracted, female](#)  
Šifra: **155828RIE**

(slika je simbolična)

### Kratek opis

Compact cyl.ISO 21287, single-acting, female piston rod, retr., magnet, Piston Ø25, Stroke 25, M5, Work.press.max.10 bar, Temp.-20°C to 70°C  
Series acc. to ISO 21287 characterised by a very short and compact design.  
The standard type features a magnetic piston.  
Piston rod optionally with male or female thread.  
Suitable for filtered, unlubricated or lubricated compressed air.  
If lubrication is used, it must be continuous.

### Tehnične Specifikacije

Min. temperaturno območje [°C]	-20
Bat	Aluminium
Batnica	S45C steel, hard chrome-plated
Batnica IT	M6x1.0
Ffunkcija	single-acting
Gewinde Kolbenstange	female piston rod with magnet
Magnet	Anodised aluminium jacket with T-slots
Ovoj	M5
Povezava	ASE series
Serija	acc. to ISO 21287
Standard	pressureless in the retracted position
Starting position	NBR
Tesnilo	10
Max. delovni tlak [bar]	25
Bat Ø [mm]	25
Stroke [mm]	25
Max. temperaturno območje [°C]	70