

Datum: 21.09.2024



## **Kompaktni cilindar, enosmerni, P-Ø 40, hod 20, G1/8,ISO21287**

Kategorija: [Compact cylinders single-acting, retracted, female](#)  
Šifra: **155837RIE**

(slika je simbolična)

### **Kratek opis**

Compact cyl.ISO 21287,single-acting,female piston rod,retr.,magnet,PistonØ40,Stroke20,G1/8,Work.press.max. 10bar,Temp.-20°C to 70°C  
Series acc. to ISO 21287 characterised by a very short and compact design.  
The standard type features a magnetic piston.  
Piston rod optionally with male or female thread.  
Suitable for filtered, unlubricated or lubricated compressed air.  
If lubrication is used, it must be continuous.

### **Tehnične Specifikacije**

Min. temperaturno območje [°C]	-20
Bat	Aluminium
Batnica	S45C steel, hard chrome-plated
Batnica IT	M8x1.25
Ffunkcija	single-acting
Gewinde Kolbenstange	female piston rod with magnet
Magnet	Anodised aluminium jacket with T-slots
Ovoj	G 1/8
Povezava	ASE series
Serija	acc. to ISO 21287
Standard	pressureless in the retracted position
Starting position	NBR
Tesnilo	10
Max. delovni tlak [bar]	20
Stroke [mm]	40
Bat Ø [mm]	70
Max. temperaturno območje [°C]	