



## **Kompaktni cilindri, enosmerni, P-Ø 63, hod 25, G1/8, ISO 21287**

Kategorija: [Compact cylinders single-acting, retracted, female](#)  
Šifra: **155848RIE**

(slika je simbolična)

### **Kratek opis**

Compact cyl.ISO 21287,single-acting,female piston rod,retr.,magnet,PistonØ63,Stroke25,G1/8,Work.press.max.10bar,Temp.-20°C to 70°C  
Series acc. to ISO 21287 characterised by a very short and compact design.  
The standard type features a magnetic piston.  
Piston rod optionally with male or female thread.  
Suitable for filtered, unlubricated or lubricated compressed air.  
If lubrication is used, it must be continuous.

### **Tehnične Specifikacije**

|                                |  |
|--------------------------------|--|
| Min. temperaturno območje [°C] | -20                                    |
| Bat                            | Aluminium                              |
| Batnica                        | S45C steel, hard chrome-plated         |
| Batnica IT                     | M10x1.5                                |
| Ffunkcija                      | single-acting                          |
| Gewinde Kolbenstange           | female piston rod with magnet          |
| Magnet                         | Anodised aluminium jacket with T-slots |
| Ovoj                           | G 1/8                                  |
| Povezava                       | ASE series                             |
| Serija                         | acc. to ISO 21287                      |
| Standard                       | pressureless in the retracted position |
| Starting position              | NBR                                    |
| Tesnilo                        | 10                                     |
| Max. delovni tlak [bar]        | 25                                     |
| Stroke [mm]                    | 63                                     |
| Bat Ø [mm]                     | 70                                     |
| Max. temperaturno območje [°C] |  |