



## Kontaktni manometer, priklp spodaj, G 1/2, 0 - 6 bar, Ø 160

Kategorija: [Wika](#)  
Šifra: **102610RIE**

(slika je simbolična)

### Kratek opis

Contact pressure gauge, magnetic spring contact, Connection radial bottom, G 1/2, Goods class 1.0, Measurement range 0-6 bar, Ø160  
Robust bourdon-tube pressure gauge with electrical contact (magnetic spring contact), contact type 821.21. The electrical contact opens an electrical circuit when the first set limit value is reached and closes it again at the second limit value.  
Suitable for gaseous or liquid media which do not corrode copper alloy, do not have high viscosity and do not crystallise.  
Current ratings:  
Make rating 1.0 A  
Break rating 1.0 A  
Continuous load 0.6 A  
Pin assignment 821.21:  
1. Contact makes when pointer reaches set point  
2. Contact breaks when pointer reaches set point

### Tehnične Specifikacije

Min. sobna temperatura [°C]	-20
Min. temperatura medija [°C]	-20
Material Prozessanschluss	Copper alloy
Merilni element	Copper alloy
Ohišje	CrNi steel 1.4301
Okvir	CrNi steel 1.4301
Položaj povezave	radial on bottom
Povezava	G 1/2
Prednje steklo	Polycarbonate
Premikanje	Copper alloy
Spodnja/Zgornja meja območja	Positive pressure
Vrsta	PGS21
Stopnja rasti na območju skale - bar [bar]	0.1
Razred točnosti	1.0
Merilno območje max. bar	6
Max. preklopna zmogljivost	30 W / 50 VA
Max. sobna temperatura [°C]	60
Max. temperatura medija [°C]	80
Premer [mm]	160
Nazivna obratovalna napetost (MSR) Ueff max. [V]	250