

Datum: 14.01.2026

Davčna št.: SI 56119488
Telefon: 01 500 14 42
E-mail: info@podjetje-trg.si
WWW: www.karcher-trg.si



Kot. pregrad. navoj. prik., M14x1.5, za 6/8 mm, AF 19, PA

Kategorija: [Bulkhead elbow couplings - polyamide](#)
Šifra: **110845RIE**

(slika je simbolična)

Kratek opis

Angled bulkhead connector, M14x1.5, for hose 6/8 mm, AF 19, Working pressure max. 10 bar (20 °C)/max. 1 bar (60 °C), PA

Manufactured from high impact-resistant, UV-stabilised engineering plastic, extremely resistant to weathering. Good chemical resistance to benzine, diesel oil, fuel oil and alkalis. Not suitable for use with acids.

Tehnične Specifikacije

Narezana matica	Polypropylene (PP)
Navoj	M14x1.5
Telo vijačnega priključka	Polyamide (PA)
Vpenjalni obroč	Polypropylene (PP)
Max. delovni tlak pri 60 ° C [bar]	1
Za cevi [mm]	6/8
Max. delovni tlak pri 20 ° C [bar]	10
a/f [mm]	19
L2 [mm]	33.0
L1 [mm]	53.0