



(slika je simbolična)

## Kot. varnos. ventil, za tekoč., G 1/2, vkl. prit. 15 bar

Kategorija: [Angle-tip Varnostni ventil G 1/2](#)  
Šifra: **105558RIE**

### Kratek opis

Corner safety valve, for liquids, Red brass, FPM, Operating temp. -10 °C to 110 °C, G 1/2, AF 27, Trigger pressure 15 bar  
For non-toxic, non-flammable liquids.  
No evaporation allowed when blowing off.  
With diaphragm to protect the spring and with lifting device.  
Type-tested, TÜV-SV. 749. F

### Tehnične Specifikacije

|                                   |   |
|-----------------------------------|---|
| Min. delovna temperatura [°C]     | -10   |
| Membrane                          | FPM   |
| Navoj                             | G 1/2   |
| Notranji deli                     | Brass   |
| Ohišje                            | Bronze  |
| Vstop in izstop                   | Each with female thread type G acc. to DIN EN ISO 228-1 |
| Vzmet                             | C steel   |
| Vzmet pokrova motorja             | Brass   |
| Min. prilagoditveno območje [bar] | 1   |
| Min. nastavljeni tlak [bar]       | 15  |
| Max. območje nastavitve [bar]     | 16  |
| L2 [mm]                           | 20.0  |
| L1 [mm]                           | 25.0  |
| a/f [mm]                          | 27  |
| H [mm]                            | 92.0  |
| Max. delovna temperatura [°C]     | 110   |