

Datum: 24.04.2026



## Kot.vijačni prik. POM, G 1/2 , zun. premera 10 mm

Kategorija: [Male elbows - POM](#)  
Šifra: **110298RIE**

(slika je simbolična)

### Kratek opis

Angled screw-in fitting POM, G 1/2 o., for hose exterior Ø 10 mm, working pressure -0.95 to 10 bar

Lightweight, push-in fittings distinguished by high strength, toughness, resistance to abrasion and impact resistance - ideal for a wide range of applications.

All our push-in fittings made of POM have the following approvals:

drinking water DVGW, KTW, FDA and NSF.

Plastic and metal tubes are connected together quickly and easily. Suitable for compressed air or liquids, with good resistance to a large number of chemicals.

### Tehnične Specifikacije

Min. delovna temperatura v zraku [°C]	-20
Min. delovni tlak [bar]	-0.95
Material	Acetal polymer (POM)
Navoj	G 1/2
Min. delovna temperatura v vodi [°C]	1
Max. delovni tlak [bar]	10
Za cevi O.D. [mm]	10
a/f [mm]	27
L1 [mm]	35.0
L2 [mm]	54.5
Max. delovna temperatura v zraku [°C]	65
Max. delovna temperatura v vodi [°C]	70