

Datum: 24.04.2026



(slika je simbolična)

Kot.vijačni prik. POM, G 1/8 , zun. premera 8 mm

Kategorija: [Male elbows - POM](#)
Šifra: **110290RIE**

Kratek opis

Angled screw-in fitting POM, G 1/8 o., for hose exterior Ø 8 mm, working pressure -0.95 to 16 bar
Lightweight, push-in fittings distinguished by high strength, toughness, resistance to abrasion and impact resistance - ideal for a wide range of applications.
All our push-in fittings made of POM have the following approvals:
drinking water DVGW, KTW, FDA and NSF.
Plastic and metal tubes are connected together quickly and easily. Suitable for compressed air or liquids, with good resistance to a large number of chemicals.

Tehnične Specifikacije

| | |
|---------------------------------------|----------------------|
| Min. delovna temperatura v zraku [°C] | -20 |
| Min. delovni tlak [bar] | -0.95 |
| Material | Acetal polymer (POM) |
| Navoj | G 1/8 |
| Min. delovna temperatura v vodi [°C] | 1 |
| Za cevi O.D. [mm] | 8 |
| Max. delovni tlak [bar] | 16 |
| a/f [mm] | 17 |
| L1 [mm] | 30.0 |
| L2 [mm] | 41.5 |
| Max. delovna temperatura v zraku [°C] | 65 |
| Max. delovna temperatura v vodi [°C] | 70 |