



(slika je simbolična)

Kotni mini krogelni ventil, vgradni, G 1/4 IT

Kategorija: [Angle mini ball valves](#)
Šifra: **103361RIE**

Kratek opis

Angled mini ball valve, Control panel integration, Brass chrome plated, Operating temp. -20°C to 80°C, G 1/4 IT, PN -0.99 - 20 bar

Tehnične Specifikacije

| | |
|-------------------------------|-----------------------------------|
| Min. delovna temperatura [°C] | -20 |
| Min. obratovalni tlak [bar] | -0.99 |
| Aplikacije | Compressed air, water, oil |
| Krogelno tesnilo | PTFE |
| Krogla | Chrome-plated brass |
| Material navojev | Nickel-plated brass |
| Navoj | G 1/4 IT |
| Ohišje | Chrome-plated brass |
| Standardni navoj | G-thread acc. to DIN EN ISO 228-1 |
| Stebelno tesnilo | NBR |
| Vrtljiva ročica | PA 66 glass fibre-reinforced |
| DN | 5 |
| a/f 1 [mm] | 17 |
| a/f 2 [mm] | 17 |
| H2 [mm] | 17.5 |
| G [mm] | 19.0 |
| Max. obratovalni tlak [bar] | 20 |
| L [mm] | 28.5 |
| H1 [mm] | 33.5 |
| Max. delovna temperatura [°C] | 80 |