



(slika je simbolična)

## Kotni mini krogelni ventil, vgradni, G 3/8 IT

Kategorija: [Angle mini ball valves](#)  
Šifra: **103362RIE**

### Kratek opis

Angled mini ball valve, Control panel integration, Brass chrome plated, Operating temp. -20°C to 80°C, G 3/8 IT, PN -0.99 - 20 bar

### Tehnične Specifikacije

|                               |                                   |
|-------------------------------|-----------------------------------|
| Min. delovna temperatura [°C] | -20                               |
| Min. obratovalni tlak [bar]   | -0.99                             |
| Aplikacije                    | Compressed air, water, oil        |
| Krogelno tesnilo              | PTFE                              |
| Krogla                        | Chrome-plated brass               |
| Material navojev              | Nickel-plated brass               |
| Navoj                         | G 3/8 IT                          |
| Ohišje                        | Chrome-plated brass               |
| Standardni navoj              | G-thread acc. to DIN EN ISO 228-1 |
| Stebelno tesnilo              | NBR                               |
| Vrtljiva ročica               | PA 66 glass fibre-reinforced      |
| DN                            | 7                                 |
| a/f 1 [mm]                    | 17                                |
| G [mm]                        | 19.0                              |
| H2 [mm]                       | 19.5                              |
| Max. obratovalni tlak [bar]   | 20                                |
| a/f 2 [mm]                    | 21                                |
| L [mm]                        | 31.0                              |
| H1 [mm]                       | 35.0                              |
| Max. delovna temperatura [°C] | 80                                |