

Datum: 21.06.2026

krog. ventil med., El. vklop 230 V AC,50 Hz, 1 1/4

Kategorija: [Brass ball valve, electric actuator 230 VAC, 50 Hz](#)
Šifra: **103697RIE**

(slika je simbolična)

Kratek opis

Brass ball valve, Electr. actuation drive, 230 V AC, 50 Hz,
Operating temperature -20 °C to 70 °C, Rp 1 1/4, DN 32, PN
max. 40 bar
Voltage range 230 VAC, 50 Hz or 24 VDC.
2-way cock, full bore, for neutral gases and liquids.
Reversible electric rotary actuator.

Tehnične Specifikacije

| | |
|-------------------------------|------------------------------|
| Min. sobna temperatura [°C] | -30 |
| Min. delovna temperatura [°C] | -20 |
| Gred izbirnika | Hard chrome-plated brass |
| Indikator položaja IP zaščita | Manually operated IP 68 |
| Krogelno tesnilo | PTFE, glass fibre-reinforced |
| Krogla | Hard chrome-plated brass |
| Material | Nickel-plated brass |
| Montažna prirobnica | ISO 5211 |
| Navoj | Rp 1 1/4 |
| Ohišje | Aluminium powder-coated |
| Tesnilo gredi izbirnika | FKM |
| Čas aktivacije [sec.] | 15 |
| D [mm] | 30.0 |
| Delovni cikel [%] | 30 |
| Relativna vlažnost | 30 % to 95 % |
| DN | 32 |
| PN [bar] | 40 |
| a/f [mm] | 50 |
| Max. delovna temperatura [°C] | 70 |
| Max. sobna temperatura [°C] | 70 |
| L [mm] | 110.0 |
| A [mm] | 153.0 |
| B [mm] | 181.5 |
| Napetost | 230 VAC, 50 Hz |